



KRAMER
on the safe side



8115

Wheel Loader

The rugged heavy-duty wheel loader.

The Kramer 8115 wheel loader belongs to the premium segment of the 8 series and is equipped with the proven principle of the undivided frame. The bucket volume of 1.15 m³ to 1.8 m³ depending on material density paired with the uniquely powerful engine option makes the 8115 a true high performance wheel loader. The optionally available ecospeed transmission and the large tires enable this machine to be used for a wide range of applications.

ecospeed transmission: The optional ecospeed transmission enables stepless acceleration from 0 km/h to 40km/h.

24 inch tires: An excellent smoothness, best traction and optimum load capacity.

Trailer hitch: The height-adjustable trailer coupling is suitable for a towing capacity of up to 14.0 t in combination with the optional air brake system.

Long loading system: The optional long loading dock allows for more overload height and range.

Versatile use: The Kramer quick hitch system allows quick change of all attachments from the wide range of products.

Technical Data

Tratarea ulterioară a gazelor de eșapament	DOC / DPF	Sarcină utilă (S=1,25 sistem de încărcare prelungit)	2,900 kg
Producător motor	Deutz	Volum rezervor combustibil	120 l
Puterea motorului	55.4 kW	Volum rezervor ulei hidraulic	64 l
Cilindree	2,925 cm ³	Viteza de deplasare standard	0-20 km/h
Puterea motorului	75 PS	Viteza de deplasare opțiunea 1	0-30 km/h
Capacitate cupă (cupă standard)	1.15 m ³	Viteza de deplasare opțiunea 2	0-40 km/h
Greutatea operațională	5,100 - 5,900 kg	Debitul sistemului hidraulic de lucru (max.)	83 l/min
Sarcină de descărcare (cupă standard)	4,250 kg	Presiunea de lucru a sistemului hidraulic de lucru (max.)	240 bar
Sarcină de descărcare (furcă pentru paletă)	3,625 kg	Cinematică de tip	P
Sarcină utilă (max.)	2,225 kg	Unghi de bracare max.	40 Grad
Sarcină utilă (S=1,25)	2,900 kg		

Dimensions

A2	Total length with standard attachment	5,800 mm
B1	Wheel base center	2,150 mm
D5	Height with cab	2,650 mm
D8	Height of cab with protective grille	2,760 mm
D9	Height with air-conditioning system	2,740 mm
D10	Height with air-conditioning system and protective grille	2,820 mm
D11	Total height with rotating beacon	2,880 mm
H1	Load-over height	3,200 mm
I1	Dumping height	2,650 mm
K1	Digging depth	45 mm
J1	Dumping width	660 mm
L1	Total width	1,970 mm
N2	Turning radius outer edge bucket	4,200 mm
M1	Ground clearance	390 mm
N1	Turning radius outer edge wheels	3,000 mm
Q2	Dumping angle at ground level	50 °
R1	Dumping angle at max. lifting height	45 °
P1	Swing angle	22 °
Z1	Stacking height	3,220 mm
Y1	Bucket width	2,150 mm