



**KRAMER**  
on the safe side



## 4209

### Telehandler

More stacking height for big jobs.

The 4209 telehandler is characterised by its huge design with a payload of 4.2 t and a stacking height of almost 9 m. Thanks to the loading system, the telehandler 4209 is the ideal machine with the plus of its transmission range. The standard equipment of the Kramer telehandler is already very extensive and, for example in addition to the ecospeed transmission, also includes the Smart Driving function.

**Differential lock:** The 100% engageable differential lock is fitted as standard, and provides maximum traction in all conditions.

**Strong braking performance:** Thanks to the multi-disc brakes in the front and rear axles. The parking brake is automatically activated when the engine stops, ensuring a high level of safety.

**Operating concept:** Color-coded switches and an electronically pre-controlled all-in-one joystick ensure intuitive operation of all functions.

**Loading system:** End position damping is integrated in all three functions which minimizes loading losses as well as optimizes motion sequences and protects the machine.

**Durability:** The torsion-resistant frame in box-section design with lateral support for the telescopic arm ensures maximum durability of the machine.

## Technical Data

Tratarea ulterioară a gazelor de eșapament	DOC / DPF / SCR	Forță de ridicare (max.)	49.7 kN
Producător motor	Deutz	Înălțime de stivuire (max.)	8,750 mm
Puterea motorului	100 kW	Volum rezervor combustibil	180 l
la turație pe minut max.	2,300 U/min	Volum rezervor ulei hidraulic	100 l
Cilindree	3,621 cm <sup>3</sup>	Volum rezervor soluție de uree	12 l
Puterea motorului	136 PS	Viteza de deplasare standard	0-30 km/h
Greutatea operațională	9,000 - 10,500 kg	Viteza de deplasare opțiunea 1	0-20 km/h
Sarcină utilă (max.)	4,200 kg	Viteza de deplasare opțiunea 2	0-40 km/h
Sarcină utilă la rază de acțiune max.	1,500 kg	Debitul sistemului hidraulic de lucru (max.)	140 l/min
Sarcină utilă la înălțime max. de stivuire	4,200 kg	Presiunea de lucru a sistemului hidraulic de lucru (max.)	215 bar
Sarcină utilă max. (LSP 500 mm)	4,200 kg	Unghi de bracare max.	38 Grad
Forță de rupere / desprindere (max.)	50.3 kN		

## Dimensions

A1	Total length	5,600 mm
A2	Total length with bucket	6,690 mm
B1	Total width without bucket	2,500 mm
C1	Front track/rear	1,995 mm
D1	Total height	2,570 mm
D2	Total height with rotating beacon	2,740 mm
E1	Cab width	990 mm
F1	Wheel base center	3,150 mm
G1	Ground clearance under axle and transmission, wading depth	412 mm
H1	Distance center rear wheel to rear	1,140 mm
I1	Rear approach angle (slope angle)	32 °
J1	Dumping angle	45 °
J2	Dumping angle	41 °
K1	Load-over height / retracted	5,545 mm
K2	Load-over height / extended	8,498 mm
L1	Dumping height / retracted	5,015 mm
L2	Dumping height / extended	7,997 mm
M1	Dumping width / extended	63 mm
N1	Tele extension length / retracted	6,277 mm
N2	Tele extension length / extended	9,243 mm
O1	Total height telescopic arm mounting in frame	1,935 mm
P1	Distance center front wheel to bucket leading edge	2,400 mm
P2	Distance center front wheel bearing quick change frame	1,310 mm
Q1	Bucket pivot point / retracted	6,116 mm
Q2	Bucket pivot point / extended	9,083 mm
R1	Turning radius outer edge wheels	4,415 mm
R2	Turning radius outer edge bucket	5,650 mm
S1	Entry height cab floor	975 mm